## 2024 JET SKI<sup>®</sup> ULTRA<sup>®</sup> 310X









Direct drive from engine

## **POWER**

		Oil Capacity	5.3 gt
Engine Displacement	Supercharged and intercooled, 4-stroke, DOHC, four valves per cylinder, inline 4- cylinder 1,498cc	Fuel Capacity Load Capacity	21.1 gal 496 lb
Bore x Stroke	83.0 x 69.2mm	Storage Capacity	44.5 gal
Compression Ratio	8.2:1	DETAILS	1
Induction	Eaton Twin Vortices Series Roots-type supercharger with air-to-water intercooler	Overall Length	135.4 in
Maximum Boost	16.8 psi	Overall Width	47.0 in
Cooling System	Inducted water	Overall Height	46.5 in
Fuel System	DFI® with 60mm throttle body	Curb Weight	1,031.9 lb*
Ignition	TCBI with Digital Advance	Seating Capacity	3
Starting System	Electric	<b>Color Choices</b>	Ebony/Neon Red
Propulsion System	160mm jet pump, axial-flow, single stage	Warranty	12 Month Limited Warranty
Impeller	3-blade, oval-edge stainless steel	Kawasaki Protection Plus™	12, 24, 36, or 48 months
PERFORMANCE		(optional)	

Coupling

## Lubrication

Semi-dry sump system



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2023 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.